

# POSSIBLE COMBINATIONS OF TIRE WIDTHS AND INNER RIM WIDTHS



Hookless or straight side rims may only be combined with TLE/TLR tires (Tubeless Easy/Tubeless Ready). Regardless of whether they are used tubeless or with tube. This restriction applies regardless of intended use (MTB, gravel/cross, city/tour, road bike).

TIRE WIDTH		INNER RIM WIDTH IN MM																												
		15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30 to 31	32 to 33	34 to 37	38 to 40	41 to 45	46 to 50	51 to 64	65 to 71	72 to 78	79 to 83	84 to 89	90 to 96	97 to 100	
from [mm]	to [mm]																													
20	21	x	x	x																										
22	24	x	x	x	x	x																								
25	27	x	x	x	x	x	x	x	x	x																				
28	28	x	x	x	x	x	x	x	x	x	x																			
29	31	x	x	x	x	x	x	x	x	x	x																			
32	34	x	x	x	x	x	x	x	x	x	x																			
35	36	x	x	x	x	x	x	x	x	x	x	x	x																	
37	39	x	x	x	x	x	x	x	x	x	x	x	x																	
40	41			x	x	x	x	x	x	x	x	x	x	x																
42	43			x	x	x	x	x	x	x	x	x	x	x																
44	46			x	x	x	x	x	x	x	x	x	x	x																
47	49			x	x	x	x	x	x	x	x	x	x	x	x	x														
50	51			x	x	x	x	x	x	x	x	x	x	x	x	x														
52	54			x	x	x	x	x	x	x	x	x	x	x	x	x														
55	57					x	x	x	x	x	x	x	x	x	x	x	x	x												
58	59					x	x	x	x	x	x	x	x	x	x	x	x	x	x											
60	61					x	x	x	x	x	x	x	x	x	x	x	x	x	x											
62	63					x	x	x	x	x	x	x	x	x	x	x	x	x	x											
64	65							x	x	x	x	x	x	x	x	x	x	x	x	x										
66	71									x	x	x	x	x	x	x	x	x	x	x	x									
72	83									x	x	x	x	x	x	x	x	x	x	x	x	x								
84	99																													
100	113																													
114	132																													

NOTE: Always consider the maximum air pressure and tire type (Tubeless/Tube Type) specifications of the rim manufacturer.