

POSSIBLE COMBINATIONS OF TIRE WIDTHS AND INNER RIM WIDTHS

Hookless or straight side rims may only be combined with TLE/TLR tires (Tubeless Easy/Tubeless Ready). Regardless of whether they are used tubeless or with tube. This restriction applies regardless of intended use (MTB, gravel/cross, city/tour, road bike).

Tire width		Inner rim width in mm																		
		15	16	17	18 to 20	21 to 22	23	24	25	26 to 27	28 to 30	31 to 35	36 to 40	41 to 43	44 to 53	54 to 58	59 to 64	65 to 71	72 to 89	90 to 100
from [mm]	to [mm]																			
20	21	x	x	x																
22	24	x	x	x	x															
25	27	x	x	x	x	x														
28	28		x	x	x	x	x													
29	34		x	x	x	x	x	x	x											
35	46			x	x	x	x	x	x	x										
47	57			x	x	x	x	x	x	x	x									
58	65					x	x	x	x	x	x	x								
66	71								x	x	x	x	x							
72	83										x	x	x	x						
84	95												x	x	x	x				
96	113																x	x	x	
114	132																		x	x

NOTE: Always consider the maximum air pressure and tire type (Tubeless/Tube Type) specifications of the rim manufacturer.

 ETRTO Standard 2024